## altımo

## Altimo TH902SS



TECHNICAL SPECIFICATION			
Type	T-Line Hood	Energy Efficiancy Class (EEI)	A
Width	900mm	Duct or Recycle Compatible	Yes
Speeds	3 Speed	Duct	Ready from factory
Control type	Soft Touch	Duct Outlet Diameter	150mm round (125mm adaptor supplied)
Extraction rate	643m3	Charcoal Filter (optional)	Altimo CF005
Illumination	2 x lamp (spot 6w LED)	Quantity Needed Per Change	1 required (1 supplied)
Installation Height - Electric Hob	65cm minimum	Voltage	AC220-240v 50hz
Installation Height - Gas Hob	75cm miminum	Motor Power	210w
Installation Template	Supplied	Lamp Power	2 x 3w
Cable termination	13a UK plug	Total Power	216w
Cable length	200cm	Annual Energy Consumption (AEC) (kWh/a)	48.2
Fluid Dynamic Efficience (FDE)	31.3	Minimum Air Flow in normal use (m3/h)	264
Fluid Dynamic Efficience Class (FDE)	Α	Maximum Air Flow in normal use (m3/h)	647
Light Efficiency (LE)	44	Sound Level at Minimum Speed (dB)	47
Light Efficiency Class (LE)	Α	Sound Level at Maximum Speed (dB)	67
Grease Filtering Efficiency (GFE)	84.1	Power Consumption in off mode (w)	0.4
Grease Filtering Efficiency Class (GFE)	С		

Please note: Extracting air through ducting does not require use of a charcoal filter. Optional charcoal filters are used to help remove cooking odours from the air before it is recycled back into the kitchen.